



SIMATIC S7-300, Front connector with screw contacts, 40-pole

General information

Product type designation Front connector

Ambient conditions

Ambient temperature during operation

- min. 0 °C
- max. 60 °C

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Accessories

belongs to product S7-300

connection method

Connection I/O signals

- Connection method Screw terminals
- Number of lines per connection 1; Or 2 cables up to 0.75 mm² (total) in a shared end sleeve

Conductor cross-section in mm²

- Connectable cable cross-sections for massive cables, min. 0.14 mm²
- Connectable cable cross-sections for massive cables, min. 0.75 mm²
- Connectable cable cross-sections for flexible cables without end sleeve, min. 0.14 mm²
- Connectable cable cross-sections for flexible cables without end sleeve, max. 0.75 mm²
- Connectable cable cross-sections for flexible cables with end sleeve, min. 0.14 mm²
- Connectable cable cross-sections for flexible cables with end sleeve, max. 0.75 mm²

Conductor cross-section acc. to AWG

- Connectable cable cross-sections for massive cables, min. 24
- Connectable cable cross-sections for massive cables, min. 19
- Connectable cable cross-sections for flexible cables without end sleeve, min. 24
- Connectable cable cross-sections for flexible cables without end sleeve, max. 19
- Connectable cable cross-sections for flexible cables with end sleeve, min. 24
- Connectable cable cross-sections for flexible cables with end sleeve, max. 19

Wire end processing

- Stripped length of cables, min. 6 mm
- Stripped length of cables, max. 6 mm

— End sleeve acc. to DIN 46228 without plastic sleeve	Design A, 5 mm to 7 mm long
— End sleeve acc. to DIN 46228 with plastic sleeve	Design E, up to 6 mm long
Mounting	
— Tool	Screwdriver, conical design, 3 mm to 3.5 mm
— Tightening torque, min.	0.4 N·m
— Tightening torque, max.	0.7 N·m
Dimensions	
Width	21.6 mm
Height	125 mm
Depth	40.9 mm
Weights	
Weight, approx.	137 g

last modified: 3/12/2024 