



Figure similar

SIMATIC S7-1200, Analog input, SM 1231, 4 AI, +/-10 V, +/-5 V, +/-2.5 V, or 0-20 mA/4-20 mA, 12 bit+sign (13 bit ADC)

General information	
Product type designation	SM 1231, AI 4x13 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	45 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	4; Current or voltage differential inputs
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	625 $\mu$ s
Input ranges	
<ul style="list-style-type: none"> <li>• Voltage</li> </ul>	Yes; $\pm 10$ V, $\pm 5$ V, $\pm 2.5$ V
<ul style="list-style-type: none"> <li>• Current</li> </ul>	Yes; 4 to 20 mA, 0 to 20 mA
<ul style="list-style-type: none"> <li>• Thermocouple</li> </ul>	No
<ul style="list-style-type: none"> <li>• Resistance thermometer</li> </ul>	No
<ul style="list-style-type: none"> <li>• Resistance</li> </ul>	No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>• -10 V to +10 V</li> </ul>	Yes
— Input resistance (-10 V to +10 V)	$\geq 9$ MOhm
<ul style="list-style-type: none"> <li>• -2.5 V to +2.5 V</li> </ul>	Yes
— Input resistance (-2.5 V to +2.5 V)	$\geq 9$ MOhm
<ul style="list-style-type: none"> <li>• -5 V to +5 V</li> </ul>	Yes
— Input resistance (-5 V to +5 V)	$\geq 9$ MOhm
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>• 0 to 20 mA</li> </ul>	Yes
— Input resistance (0 to 20 mA)	280 $\Omega$
<ul style="list-style-type: none"> <li>• 4 mA to 20 mA</li> </ul>	Yes
— Input resistance (4 mA to 20 mA)	280 $\Omega$
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> </ul>	12 bit; + sign
<ul style="list-style-type: none"> <li>• Integration time, parameterizable</li> </ul>	Yes

<ul style="list-style-type: none"> <li>Interference voltage suppression for interference frequency <math>f_1</math> in Hz</li> </ul>	40 dB, DC to 60 V for interference frequency 50 / 60 Hz
<b>Smoothing of measured values</b>	
<ul style="list-style-type: none"> <li>parameterizable</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Step: None</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Step: low</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Step: Medium</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Step: High</li> </ul>	Yes
<b>Errors/accuracies</b>	
Temperature error (relative to input range), (+/-)	25 °C $\pm$ 0.1%, to 55 °C $\pm$ 0.2% total measurement range
<b>Basic error limit (operational limit at 25 °C)</b>	
<ul style="list-style-type: none"> <li>Voltage, relative to input range, (+/-)</li> </ul>	0.1 %
<ul style="list-style-type: none"> <li>Current, relative to input range, (+/-)</li> </ul>	0.1 %
<b>Interference voltage suppression for <math>f = n \times (f_1 \pm 1 \%)</math>, <math>f_1</math> = interference frequency</b>	
<ul style="list-style-type: none"> <li>Common mode voltage, max.</li> </ul>	12 V
<b>Interrupts/diagnostics/status information</b>	
Alarms	Yes
Diagnostics function	Yes
<b>Alarms</b>	
<ul style="list-style-type: none"> <li>Diagnostic alarm</li> </ul>	Yes
<b>Diagnoses</b>	
<ul style="list-style-type: none"> <li>Monitoring the supply voltage</li> </ul>	Yes
<ul style="list-style-type: none"> <li>Wire break</li> </ul>	Yes
<b>Diagnostics indication LED</b>	
<ul style="list-style-type: none"> <li>for status of the inputs</li> </ul>	Yes
<ul style="list-style-type: none"> <li>for maintenance</li> </ul>	Yes
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
<b>Ecological footprint</b>	
<ul style="list-style-type: none"> <li>environmental product declaration</li> </ul>	Yes
<b>Global warming potential</b>	
— global warming potential, (total) [CO2 eq]	43.1 kg
— global warming potential, (during production) [CO2 eq]	7.62 kg
— global warming potential, (during operation) [CO2 eq]	36 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.544 kg
<b>Ambient conditions</b>	
<b>Free fall</b>	
<ul style="list-style-type: none"> <li>Fall height, max.</li> </ul>	0.3 m; five times, in product package
<b>Ambient temperature during operation</b>	
<ul style="list-style-type: none"> <li>min.</li> </ul>	-20 °C
<ul style="list-style-type: none"> <li>max.</li> </ul>	60 °C
<ul style="list-style-type: none"> <li>horizontal installation, min.</li> </ul>	-20 °C
<ul style="list-style-type: none"> <li>horizontal installation, max.</li> </ul>	60 °C
<ul style="list-style-type: none"> <li>vertical installation, min.</li> </ul>	-20 °C
<ul style="list-style-type: none"> <li>vertical installation, max.</li> </ul>	50 °C
<b>Ambient temperature during storage/transportation</b>	
<ul style="list-style-type: none"> <li>min.</li> </ul>	-40 °C
<ul style="list-style-type: none"> <li>max.</li> </ul>	70 °C

Air pressure acc. to IEC 60068-2-13	
• Operation, min.	795 hPa
• Operation, max.	1 080 hPa
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
Relative humidity	
• Operation at 25 °C without condensation, max.	95 %
Pollutant concentrations	
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free
Connection method	
required front connector	Yes
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
Dimensions	
Width	45 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	180 g
Classifications	

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

Approvals / Certificates			
General Product Approval	Maritime application	other	Environment



[Confirmation](#)



[Confirmation](#)



[Environmental Confirmations](#)

last modified:

5/16/2025