



Figure similar

SIMATIC S7-1200, Analog input, SM 1231, 4 AI, +/-10 V, +/-5 V, +/-2.5 V, +/-1.25 V or 0-20 mA/4-20 mA, 15 bit+sign bit

General information	
Product type designation	SM 1231, AI 4x16 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	65 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	1.8 W
Analog inputs	
Number of analog inputs	4; Current or voltage differential inputs
permissible input voltage for voltage input (destruction limit), max.	±35 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	100 µs
Input ranges	
<ul style="list-style-type: none"> • Voltage 	Yes; ±10V, ±5V, ±2.5V or ±1.25V
<ul style="list-style-type: none"> • Current 	Yes; 4 to 20 mA, 0 to 20 mA
<ul style="list-style-type: none"> • Thermocouple 	No
<ul style="list-style-type: none"> • Resistance thermometer 	No
<ul style="list-style-type: none"> • Resistance 	No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • -1.25 V to +1.25 V 	Yes
<ul style="list-style-type: none"> • -10 V to +10 V 	Yes
— Input resistance (-10 V to +10 V)	≥1 MOhm
<ul style="list-style-type: none"> • -2.5 V to +2.5 V 	Yes
— Input resistance (-2.5 V to +2.5 V)	≥1 MOhm
<ul style="list-style-type: none"> • -5 V to +5 V 	Yes
— Input resistance (-5 V to +5 V)	≥1 MOhm
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA 	Yes
<ul style="list-style-type: none"> • 4 mA to 20 mA 	Yes
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. 	15 bit; + sign
<ul style="list-style-type: none"> • Integration time, parameterizable 	Yes
<ul style="list-style-type: none"> • Interference voltage suppression for interference frequency f1 in Hz 	40 dB, DC to 60 V for interference frequency 50 / 60 Hz

Smoothing of measured values	
• parameterizable	Yes
• Step: None	Yes
• Step: low	Yes
• Step: Medium	Yes
• Step: High	Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	25 °C ±0.1% / ±0.3% total measurement range
Basic error limit (operational limit at 25 °C)	
• Voltage, relative to input range, (+/-)	0.1 %
• Current, relative to input range, (+/-)	0.1 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency	
• Common mode voltage, max.	12 V
Interrupts/diagnostics/status information	
Alarms	Yes
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnoses	
• Monitoring the supply voltage	Yes
• Wire break	Yes
Diagnostics indication LED	
• for status of the inputs	Yes
• for maintenance	Yes
Degree and class of protection	
IP degree of protection	IP20
Standards, approvals, certificates	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
Ecological footprint	
• environmental product declaration	Yes
Global warming potential	
— global warming potential, (total) [CO2 eq]	43.1 kg
— global warming potential, (during production) [CO2 eq]	7.62 kg
— global warming potential, (during operation) [CO2 eq]	36 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.544 kg
Ambient conditions	
Free fall	
• Fall height, max.	0.3 m; five times, in product package
Ambient temperature during operation	
• min.	-20 °C
• max.	60 °C
• horizontal installation, min.	-20 °C
• horizontal installation, max.	60 °C
• vertical installation, min.	-20 °C
• vertical installation, max.	50 °C
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	70 °C
Air pressure acc. to IEC 60068-2-13	

• Operation, min.	795 hPa
• Operation, max.	1 080 hPa
• Storage/transport, min.	660 hPa
• Storage/transport, max.	1 080 hPa
Relative humidity	
• Operation at 25 °C without condensation, max.	95 %
Pollutant concentrations	
• SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free
Connection method	
required front connector	Yes
Mechanics/material	
Enclosure material (front)	
• Plastic	Yes
Dimensions	
Width	45 mm
Height	100 mm
Depth	75 mm
Weights	
Weight, approx.	180 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	10	EC001420
	ETIM	9	EC001420
	ETIM	8	EC001420
	ETIM	7	EC001420
	IDEA	4	3562
	UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



EG-Konf.



[Manufacturer Declaration](#)

[Miscellaneous](#)



UL

[Metrological Approval](#)

General Product Approval **EMV** **For use in hazardous locations**



RCM



[China RoHS](#)

[Manufacturer Declaration](#)



RCM



ATEX

For use in hazardous locations **Maritime application**



IECEX

[EM](#)



UL

[Miscellaneous](#)

[CCC-Ex](#)



DNV



[KR \(Korean Register of Shipping\)](#)



last modified:

7/2/2025