



SIMATIC S7-1200, analog I/O SM 1234, 4 AI/2 AO, +/-10 V, 14-bit resolution or 0 (4)-20mA, 13-bit resolution

General information	
Product type designation	SM 1234, AI 4x13 bit/AQ 2x14 bit
Supply voltage	
Rated value (DC)	24 V
Input current	
Current consumption, typ.	60 mA
from backplane bus 5 V DC, typ.	80 mA
Power loss	
Power loss, typ.	2 W
Analog inputs	
Number of analog inputs	4; Current or voltage differential inputs
permissible input voltage for voltage input (destruction limit), max.	35 V
permissible input current for current input (destruction limit), max.	40 mA
Cycle time (all channels) max.	625 $\mu$ s
Input ranges	
<ul style="list-style-type: none"> <li>• Voltage</li> </ul>	Yes; $\pm 10$ V, $\pm 5$ V, $\pm 2.5$ V
<ul style="list-style-type: none"> <li>• Current</li> </ul>	Yes; 4 to 20 mA, 0 to 20 mA
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> <li>• -10 V to +10 V</li> <li>— Input resistance (-10 V to +10 V)</li> </ul>	Yes $\geq 9$ MOhm
<ul style="list-style-type: none"> <li>• -2.5 V to +2.5 V</li> <li>— Input resistance (-2.5 V to +2.5 V)</li> </ul>	Yes $\geq 9$ MOhm
<ul style="list-style-type: none"> <li>• -5 V to +5 V</li> <li>— Input resistance (-5 V to +5 V)</li> </ul>	Yes $\geq 9$ MOhm
Input ranges (rated values), currents	
<ul style="list-style-type: none"> <li>• 0 to 20 mA</li> <li>— Input resistance (0 to 20 mA)</li> </ul>	Yes 280 $\Omega$
<ul style="list-style-type: none"> <li>• 4 mA to 20 mA</li> </ul>	Yes
Analog outputs	
Number of analog outputs	2; Current or voltage
Output ranges, voltage	
<ul style="list-style-type: none"> <li>• -10 V to +10 V</li> </ul>	Yes
Output ranges, current	
<ul style="list-style-type: none"> <li>• 0 to 20 mA</li> <li>• 4 mA to 20 mA</li> </ul>	Yes Yes
Load impedance (in rated range of output)	
<ul style="list-style-type: none"> <li>• with voltage outputs, min.</li> </ul>	1 000 $\Omega$

• with current outputs, max.	600 Ω
<b>Cable length</b>	
• shielded, max.	100 m; shielded, twisted pair
<b>Analog value generation for the inputs</b>	
Measurement principle	Differential
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	12 bit; + sign
• Integration time, parameterizable	Yes
• Interference voltage suppression for interference frequency f1 in Hz	40 dB, DC to 60 V for interference frequency 50 / 60 Hz
<b>Smoothing of measured values</b>	
• parameterizable	Yes
• Step: None	Yes
• Step: low	Yes
• Step: Medium	Yes
• Step: High	Yes
<b>Analog value generation for the outputs</b>	
<b>Integration and conversion time/resolution per channel</b>	
• Resolution with overrange (bit including sign), max.	14 bit; Voltage: 14 bit; Current : 13 bit
<b>Errors/accuracies</b>	
Temperature error (relative to input range), (+/-)	25 °C ±0.1%, to 55 °C ±0.2% total measurement range
Temperature error (relative to output range), (+/-)	25 °C ±0.3%, to 55 °C ±0.6% total measurement range
<b>Basic error limit (operational limit at 25 °C)</b>	
• Voltage, relative to input range, (+/-)	0.1 %
• Current, relative to input range, (+/-)	0.1 %
• Voltage, relative to output range, (+/-)	0.3 %
• Current, relative to output range, (+/-)	0.3 %
<b>Interference voltage suppression for <math>f = n \times (f1 \pm 1 \%)</math>, f1 = interference frequency</b>	
• Common mode voltage, max.	12 V
<b>Interrupts/diagnostics/status information</b>	
Alarms	Yes
Diagnostics function	Yes
<b>Alarms</b>	
• Diagnostic alarm	Yes
<b>Diagnoses</b>	
• Monitoring the supply voltage	Yes
• Wire break	Yes
• Short-circuit	Yes
<b>Diagnostics indication LED</b>	
• for status of the inputs	Yes
• for status of the outputs	Yes
• for maintenance	Yes
<b>Potential separation</b>	
<b>Potential separation analog outputs</b>	
• between the channels and the power supply of the electronics	No
<b>Degree and class of protection</b>	
IP degree of protection	IP20
<b>Standards, approvals, certificates</b>	
CE mark	Yes
CSA approval	Yes
UL approval	Yes
cULus	Yes
FM approval	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
Marine approval	Yes
<b>Ecological footprint</b>	
• environmental product declaration	Yes

<b>Global warming potential</b>	
— global warming potential, (total) [CO2 eq]	43.1 kg
— global warming potential, (during production) [CO2 eq]	7.62 kg
— global warming potential, (during operation) [CO2 eq]	36 kg
— global warming potential, (after end of life cycle) [CO2 eq]	-0.544 kg

**Ambient conditions**

**Free fall**

- Fall height, max. 0.3 m; five times, in product package

**Ambient temperature during operation**

- min. -20 °C
- max. 60 °C
- horizontal installation, min. -20 °C
- horizontal installation, max. 60 °C
- vertical installation, min. -20 °C
- vertical installation, max. 50 °C

**Ambient temperature during storage/transportation**

- min. -40 °C
- max. 70 °C

**Air pressure acc. to IEC 60068-2-13**

- Operation, min. 795 hPa
- Operation, max. 1 080 hPa
- Storage/transport, min. 660 hPa
- Storage/transport, max. 1 080 hPa

**Relative humidity**

- Operation at 25 °C without condensation, max. 95 %

**Pollutant concentrations**

- SO2 at RH < 60% without condensation SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60 % condensation-free

**Connection method**

required front connector Yes

**Mechanics/material**

Enclosure material (front)  
 • Plastic Yes

**Dimensions**

Width 45 mm  
 Height 100 mm  
 Depth 75 mm

**Weights**

Weight, approx. 220 g

**Classifications**

	Version	Classification
eClass	14	27-24-22-01
eClass	12	27-24-22-01
eClass	9.1	27-24-22-01
eClass	9	27-24-22-01
eClass	8	27-24-22-01
eClass	7.1	27-24-22-01
eClass	6	27-24-22-01
ETIM	10	EC001420
ETIM	9	EC001420
ETIM	8	EC001420
ETIM	7	EC001420
IDEA	4	3562
UNSPSC	15	32-15-17-05

**Approvals / Certificates**

General Product Approval



[Miscellaneous](#)

[Manufacturer Declaration](#)



[Metrological Approval](#)

General Product Approval

EMV

For use in hazardous locations



[China RoHS](#)

[Manufacturer Declaration](#)



For use in hazardous locations

Maritime application



[EM](#)



[Miscellaneous](#)

[CCC-Ex](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)

Maritime application

Environment

[KR \(Korean Register of Shipping\)](#)



last modified:

5/16/2025